


## OKS 1110 Multi-Silicone Grease



### Description

Highly adhesive transparent silicone grease for fittings, seals and plastic parts.

### Applications

- Sealant and lubricant for cold and hot-water valves in vehicle heating systems or cooling circuits and for ground seals on glass taps and desiccators
- Lubrication of O-rings and rubber seals for assembly and during operation
- Lubrication of plastic parts

### Branches

- Glass and foundry industry
- Shipbuilding and marine technology
- Paper and packaging industry
- Rubber and plastic processing
- Rail vehicle technology
- Logistics
- Chemical industry
- Plant and machine (tool) engineering
- Iron and steel industry
- Municipal services
- Catering equipment and food processing technology

### Advantages and benefits

- NSF H1 registered
- Tasteless and odourless
- Highly effective due to excellent adhesion on all materials
- Neutral behaviour with regard to plastics and elastomers
- Completely EPDM-compatible
- High long-term stability without drying out, hardening or bleeding
- Resistant to cold and hot water, as well as acetone, ethanol, ethylene glycol, glycerine and methanol

### Application tips

Clean the lubricating points well for optimal effect. Apply the grease evenly and thinly to the functional surfaces with a brush, spatula, etc. Avoid excesses. In as far as available, observe the machine manufacturer's instructions. Assess the lubrication frequency and quantity on basis of service conditions. Only mix with suitable lubricants. Caution: Plastic based on silicone, such as silicone rubber can be attacked by silicone grease. Silicone grease may not be used at sliding points under pure oxygen influence.



# PRODUCT INFORMATION

## OKS 1110 Multi-Silicone Grease

### Packaging

- 10 ml Tube
- 80 ml Tube
- 400 ml Cartridge
- 4 g Tube
- 500 g Can
- 1 kg Can
- 5 kg Hobbock
- 25 kg Hobbock
- 180 kg Drum

### Technical Data

	Standard	Conditions	Unit	Value
<b>Main components</b>				
base oil				polydimethylsiloxane
thickener				inorganic
<b>Application related technical data</b>				
SKF-EMCOR	DIN 51 802		corr. degree	3-4
colour				transparent
consistency	DIN 51 818	DIN ISO 2137	NLGI grade	3
density (at 20°C)	DIN EN ISO 3838		g/cm <sup>3</sup>	0.96
drop point	DIN ISO 2176		°C	without
flow pressure	DIN 51 805	-40°C		< 100
flow pressure	DIN 51 805	20°C		50
lower operating temperature			°C	-40
marking	DIN 51 502	DIN 51 825		MSI3S-40
oil separation	DIN 51 817	18h/40°C	percent in weight	0.86
oil separation	DIN 51 817	168h/40°C	percent in weight	3.46
resistance to oxidation	DIN 51 808	100h/99°C	bar	< 0.3
unworked penetration	DIN ISO 2137		0.1 mm	180-210
upper operating temperature			°C	200
viscosity at (100°C)	DIN 51 562-1	base oil	mm <sup>2</sup> /s	3,800
viscosity at (40°C)	DIN 51 562-1	base oil	mm <sup>2</sup> /s	9,500
water resistance	DIN 51 807-1	90°C	Degree	0-90
<b>Product specific technical data</b>				
evaporation loss	DIN 58 397-1	30h, 200°C	percent in weight	< 2.5
<b>Properties and approvals</b>				
approval for food processing technology				NSF H1, Reg.-Nr. 124381
beer foam compatibility				approval of the BPV Weihenstephan
drinking water approval	UBA guideline (D)			test certificate KA 432
drinking water approval	ACS-conformity to positive lists (F)			test certificate 17 CLP NY 015



## OKS 1110 Multi-Silicone Grease

---

### OKS Spezialschmierstoffe GmbH

Ganghoferstraße 47  
82216 Maisach  
Phone: +49 (0) 8142 3051 - 500  
info@oks-germany.com  
[www.oks-germany.com](http://www.oks-germany.com)



The information in this publication reflects state-of-the-art technology, as well as extensive testing and experience. Due to the diversity of possible applications and technical realities, they can only serve as recommendations and are not arbitrarily transferable. Therefore, no obligations, liability or warranty claims can be derived from them. We only accept liability for the suitability of our products for particular purposes, and for certain properties of our products, in the event that we have accepted such liability in writing in the individual case. Any case of justified warranty claims shall be limited to the delivery of replacement goods free of defects, in the event that this subsequent improvement fails, to reimbursement of the purchase price. Any and all further claims, in particular the liability for consequential injuries or damage, shall always be excluded. Prior to use, the customer must conduct its own testing to prove suitability. The data are subject to change for the sake of progress. ® = Registered trademark

**Safety data sheet** for industrial and commercial users is available for downloading under [www.oks-germany.com](http://www.oks-germany.com).

Our Customer and Technical service will be pleased to help should you have any further questions.