

OKS 601 Multi Oil, Spray



Description

Low-viscosity light-coloured multipurpose oil for a wide range of applications in industrial maintenance and in the workshop field.

Applications

- For cleaning and care of metal surfaces
- Dismantling rusted-in parts
- Protects electrical contacts
- Temporary corrosion protection for bare metal surfaces
- Elimination of squeaking noises
- Lubrication of friction points at moving machine parts

Advantages and benefits

- Broad range of uses (6-fold action)
- Highly effective due to very good creep properties
- Also infiltrates strong oil and greasy soiling
- Good lubricating properties thanks to high oil percentage
- Displaces moisture
- OKS 600 is suitable for use with the OKS Airspray system

Branches

- Municipal services
- Iron and steel industry
- Paper and packaging industry
- Rubber and plastic processing
- Glass and foundry industry
- Rail vehicle technology
- Shipbuilding and marine technology
- Logistics
- Chemical industry
- Plant and machine (tool) engineering
- Maintenance and servicing

Application tips

For optimum effectiveness, first clean contamination away from surface mechanically. Apply OKS 600 generously with a brush, drip oiler, oil can or by immersion. Spray OKS 601 on. Allow to work in for time corresponding to depth of penetration required. If necessary, repeat the application several times. Apply in sufficient quantities for lubrication. Caution: Only mix with suitable lubricants.



OKS 601
Multi Oil, Spray

Packaging

- 400 ml Spray

Technical Data

	Standard	Conditions	Unit	Value
Main components				
base oil				mineral oil
Application related technical data				
coefficient of friction SRV	DIN 51 834-2	ball, disk	μ	0.09
colour				brownish transparent
density (at 20°C)	DIN EN ISO 3838		g/cm ³	0.81
flashing point	DIN EN 22 719		°C	> 64
lower operating temperature			°C	-30
marking	analogue to DIN 51 502			CL 3
salt spray test	DIN EN ISO 9227		h	> 50
upper operating temperature			°C	60
viscosity at (40°C)	DIN 51 562-1		mm ² /s	approx. 3
wear SRV	DIN 51 834-2	ball, disk		< 0.003

OKS Spezialschmierstoffe GmbH

Ganghoferstraße 47
82216 Maisach
Phone: +49 (0) 8142 3051 - 500
info@oks-germany.com
www.oks-germany.com



The information in this publication reflects state-of-the-art technology, as well as extensive testing and experience. Due to the diversity of possible applications and technical realities, they can only serve as recommendations and are not arbitrarily transferable. Therefore, no obligations, liability or warranty claims can be derived from them. We only accept liability for the suitability of our products for particular purposes, and for certain properties of our products, in the event that we have accepted such liability in writing in the individual case. Any case of justified warranty claims shall be limited to the delivery of replacement goods free of defects, in the event that this subsequent improvement fails, to reimbursement of the purchase price. Any and all further claims, in particular the liability for consequential injuries or damage, shall always be excluded. Prior to use, the customer must conduct its own testing to prove suitability. The data are subject to change for the sake of progress. ® = Registered trademark

Safety data sheet for industrial and commercial users is available for downloading under www.oks-germany.com.

Our Customer and Technical service will be pleased to help should you have any further questions.